




DS 500 - Intelligent chart recorder for compressed air and gases

Measurement - control - indication - alarm - recording - evaluation



Advantages at a glance:

- **Clear layout:** 7" colour screen with touch panel...
- **Versatile:** Up to 12 optional sensors can be connected
- **Suitable for industrial applications:** Metal housing IP 65 or panel mounting...
- **Data available through world wide web:** Network-compatible and remote transmission via web-server
- **Mathematical function:** for internal calculations
- **Totaliser function:** for analogue signals
- **...saves time and costs during installation**

DS 500 - the intelligent chart recorder of the next generation

Recording of the measured data, indication on a big colour screen, alerting, storage, not to mention remote read-out via webserver... this is all possible with DS 500.

All measured values, measurement curves and threshold value exceedances are indicated. The curve progressions from the beginning of the measurement can be viewed by an easy slide of the finger.

The big difference to ordinary paperless chart recorders reveals in the easy initiation and in the evaluation of the measured data. All sensors are identified directly and powered by DS 500. Everything is matched and tuned.

Mathematical function for internal calculations, e.g. the typical figures of a compressed air system:

- costs in € per generated m^3 air
- kWh/ m^3 generated air
- consumption of single lines including summation

Totaliser function for analogue signals (e.g. 0/4...20 mA, 0...10 V). In case of third-party sensors which e.g. only give a 4...20 mA signal for the actual flow in m^3/h , a total counter reading in m^3 can be generated by means of the totaliser function.

No time consuming studying of the instruction manual... this saves time. Internal voltage supply of all sensors, no wiring of external mains units ... this saves additional costs.

Flow meters for compressed air and gases

- Installation and removal under pressure via standard 1/2" ball valve
- A safety ring prevents the uncontrolled ejection in case of installation/removal under pressure
- Usable for different gases: Compressed air, nitrogen, argon, CO₂, oxygen...



Dew point sensors

- Extremely stable in the long term
- Quick adaption time
- Large measuring range (-80° to +20 °Ctd)
- For all dryers: (Adsorption dryers, membrane dryers and refrigeration dryers)
- Easy installation under pressure via the measuring chamber with quick coupling



Pressure sensors

- Large selection of pressure sensors with different measuring ranges for each measuring purpose
- Quick installation under pressure by quick coupling
- Pressure probe 0-10/16/40/100/250/400 bar overpressure
- Pressure probe -1 to +15 bar (underpressure/overpressure)
- Differential pressure 0...1.6 bar
- Absolute pressure 0 - 1.6 bar (abs)



- Large selection of temperature sensors e.g. for measurement of the ambient temperature or gas temperature
- Pt100 (2-wire or 3-wire)
- Pt1000 (2-wire or 3-wire)
- Temperature sensors with measuring transducer (4-20 mA output)




Temperature sensors



- Monitoring of compressed air quality according to ISO 8573
- Residual oil, particles, residual moisture



Compressed air quality measurement



- CS PM5110 current/effective power meters for panel mounting
- External current transformers for encompassing the phases (max. 2000 A)
- Measures kW, kWh, cos phi, kVar, kVA
- Data transfer DS 500 via Modbus



Current/effective power meters

By means of the intelligent chart recorder **DS 500**, all measuring data of a compressor station can be recorded, indicated and evaluated.

At **12 freely assignable sensor inputs**, all our sensors can be connected as well as any optional **third-party sensors and meters with the following signal outputs:**

4-20 mA, 0-20 mA | 0-1 V / 0-10 V / 0-30 V | Pt 100 (2- or 3-wire), Pt 1000 (2- or 3-wire), pulse outputs (e.g. of gas meters) | Modbus protocol.




Measured values, statistics, curves with the 7" colour screen with touch panel

| A1 Compressed Air | | A2 Compressed Air | | A3 Compressed Air | | A4 Compressed Air | |
|---|---------------|---|---------------|---|---------------|---|---------------|
| <input checked="" type="checkbox"/> A1a | 237.7 m³/h | <input checked="" type="checkbox"/> A2a | 729.702 m³/h | <input checked="" type="checkbox"/> A3a | 537.0 m³/h | <input checked="" type="checkbox"/> A4a | 254.7 m³/h |
| <input checked="" type="checkbox"/> -- | 34106 m³ | <input checked="" type="checkbox"/> -- | 13423271 m³ | <input checked="" type="checkbox"/> -- | 155132 m³ | <input checked="" type="checkbox"/> -- | 55234063 m³ |
| B1 Nitrogen | | B2 Nitrogen | | B3 Nitrogen | | B4 Nitrogen | |
| <input checked="" type="checkbox"/> B1a | 337.7 ltr/min | <input checked="" type="checkbox"/> B2a | 657.7 ltr/min | <input checked="" type="checkbox"/> B3a | 15.7 ltr/min | <input checked="" type="checkbox"/> B4a | 237.7 ltr/min |
| <input checked="" type="checkbox"/> -- | 27734 ltr | <input checked="" type="checkbox"/> -- | 240041 ltr | <input checked="" type="checkbox"/> -- | 34131 ltr | <input checked="" type="checkbox"/> -- | 235322 ltr |
| C1 Oxygen | | C2 Oxygen | | C3 Oxygen | | C4 Oxygen | |
| <input checked="" type="checkbox"/> C1a | 17.7 ltr/min | <input checked="" type="checkbox"/> C2a | 37.7 ltr/min | <input checked="" type="checkbox"/> C3a | 223.7 ltr/min | <input checked="" type="checkbox"/> C4a | 75.8 ltr/min |
| <input checked="" type="checkbox"/> -- | 4080 ltr | <input checked="" type="checkbox"/> -- | 234108 ltr | <input checked="" type="checkbox"/> -- | 3749 ltr | <input checked="" type="checkbox"/> -- | 43584 ltr |

Zurück Virtuelle Kanäle Alarm Lp.stop days, inte... 24.03.2014 16:41:52


Actual measured values

All measured values can be seen at a glance. Threshold value exceedances are indicated in red color. A „measuring site name“ can be allocated to each sensor.



Graphic display

This display replaces the former evaluation of ordinary paper chart recorders and offers lots of advantages. The time axis can be moved by a finger slide. The „zoom function by finger movement“ which enables an analysis of peak values is unique.



Actual measured values and graphic

Additionally to the measurement curves, the current measured values are indicated as well.

Alarm settings for channel A1 (DewPoint)

| Upper limit | Value °C/d | Hysteresis +/- | Relay 1 | Relay 2 | Relay 3 | Relay 4 |
|---|------------|----------------|--|--|--------------------------|--------------------------|
| <input checked="" type="checkbox"/> Alarm 1 | -40.000 | - 0.500 | <input checked="" type="checkbox"/> T0 | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| <input checked="" type="checkbox"/> Alarm 2 | -30.000 | - 0.500 | <input type="checkbox"/> | <input checked="" type="checkbox"/> T0 | <input type="checkbox"/> | <input type="checkbox"/> |
| Lower limit | Value °C/d | Hysteresis +/- | Relay 1 | Relay 2 | Relay 3 | Relay 4 |
| <input type="checkbox"/> Alarm 1 | 0.000 | + 0.000 | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| <input type="checkbox"/> Alarm 2 | 0.000 | + 0.000 | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

OK Cancel Setup Delay

Adjustment of the alarm relays

Each one of the four alarm relays can be allocated individually to a connected sensor. The alarm thresholds and the hysteresis can be freely adjusted.

New: It is possible to set an alarm delay for each alarm relay so that the relay is only triggered after that period of time.



Technical data of the DS 500

| TECHNICAL DATA DS 500 | |
|-----------------------------------|---|
| Dimensions of housing: | 280 x 170 x 90 mm, IP 65 |
| Connections: | 18 x PG for sensors and supply |
| Version panel mounting: | Cutout panel 250 x 156 mm |
| Weight: | 7.3 kg |
| Material: | Die cast metal, front screen polyester |
| Sensor inputs: | <ul style="list-style-type: none"> • 4/8/12 sensor inputs for analogue and digital sensors; freely allocatable. See options • Digital CS sensors for dew point and consumption with SDI interface FA/VA series, • digital third-party sensors RS 485 / Modbus RTU, other bus systems realizable on request. • Analogue CS Sensors for pressure, temperature, clamp-on ammeters pre-configured. • Analogue third-party sensors 0/4...20 mA, 0...1/10/30 V, pulse, Pt 100 / Pt 1000, KTY |
| Voltage supply for sensor: | 24 VDC, max. 130 mA per sensor, integrated mains unit max. 24 VDC, 25 W. In case of version 8/12 sensor inputs, 2 integrated mains units each max. 24 VDC, 25 W. |
| Interfaces: | USB stick, Ethernet / RS 485 Modbus-RTU / TCP, SDI other bus systems on request, webserver optional |
| Outputs: | <ul style="list-style-type: none"> • 4 relays (changeover contact 230 VAC, 6 A), alarm management, relays freely programmable, collective alarm • Analog output, pulse in case of sensors with own signal output looped, such as e.g. VA/FA series |
| Memory card: | Memory size 8 GB Micro SD card |
| Power supply: | 100...240 VAC / 50-60 Hz, special version 24 VDC |
| Colour screen: | 7" touch panel TFT transmissive, graphics, curves, statistics |
| Accuracy: | see sensor specifications |
| Operating temperature: | 0...50 °C |
| Storage temperature: | -20...70 °C |
| Optional: | Web server |

| DESCRIPTION | ORDER NO. |
|--|-----------|
| DS 500 - intelligent chart recorder in basic version (4 sensor inputs) | 0500 5000 |
| Option: 4 additional sensor inputs for DS 500 V2 | Z500 5501 |
| Option: 8 additional sensor inputs for DS 500 V2 | Z500 5502 |
| Option: Integrated webserver | Z500 5003 |
| Option: version for panel mounting | Z500 5006 |
| Option: Power supply 24 VDC (instead of 100...240 VAC) | Z500 5007 |
| Option: "Mathematics calculation function" for 4 freely selectable channels, (virtual channels): addition, subtraction, division, multiplication | Z500 5008 |
| Option: "Totaliser function for analogue signals" | Z500 5009 |
| External Gateway Profibus for connecting an integrated RS 485 interface | Z500 3008 |
| CS Basic – data evaluation graphically and in tabular form - reading of the measured data via USB or Ethernet, license for 2 workstations | 0554 8040 |
| CS Network – energy monitoring with client/server solution (max. 20 measured values of different sensors/devices) | 0554 8041 |
| CS Network – energy monitoring with client/server solution (max. 50 measured values of different sensors/devices) | 0554 8042 |
| CS Network – energy monitoring with client/server solution (max. 100 measured values of different sensors/devices) | 0554 8043 |
| CS Network - Energy Monitoring with Client / Server Solution (max. 200 measured values of different sensors / devices) | 0554 8044 |

Matching sensors can be found on pages 18 to 20

| INPUT SIGNALS | |
|-----------------------------------|--|
| Current signals | (0...20 mA / 4...20 mA) |
| Internal or external power supply | |
| Measuring range | |
| Resolution | 0...20 mA |
| Accuracy | 0.0001 mA |
| Input resistance | ± 0.03 mA ± 0.05 % 50 Ω |
| Voltage signal: | (0...1 V) |
| Measuring range | 0...1 V |
| Resolution | 0.05 mV |
| Accuracy | ± 0.2 mV ± 0.05 % |
| Input resistance | 100 kΩ |
| Voltage signal | (0...10 V / 30 V) |
| Measuring range | 0...10 V |
| Resolution | 0.5 mV |
| Accuracy | ± 2 mV ± 0.05 % |
| Input resistance | 1 MΩ |
| RTD Pt 100 | |
| Measuring range | -200...850 °C |
| Resolution | 0.1 °C |
| Accuracy | ± 0.2 °C (-100... 400 °C) ± 0.3 °C (further range) |
| RTD Pt 1000 | |
| Measuring range | -200...850 °C |
| Resolution | 0.1 °C |
| Accuracy | ± 0.2 °C (-100...400 °C) |
| Pulse | |
| Measuring range | Min pulse length 500 µs frequency 0...1 kHz max. 30 VDC |